## SILVER® EX01

## Rigid Polyvinyl Chloride

Guangdong Silver Age Sci & Tech. Co., Ltd

## Message:

SILVER® Rigid PVC 730 is a kind of flame resistant rigid PVC compound of excellent mechanical properties, good processability and heat stability, which is applied to appliance, automotive, business equipment, construction and telecommunication.

General Information			
Features	Flame Retardant		
	Good Processability		
	Good Thermal Stability		
	Medium Rigidity		
Uses	Appliances		
	Automotive Applications		
	Business Equipment		
	Construction Applications		
	Telecommunications		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	
Specific Gravity	1.28	g/cm³	
Mechanical	Nominal Value	Unit	
Tensile Strength	42.0	MPa	
Tensile Elongation (Break)	55	%	
Flexural Modulus	2200	MPa	
Flexural Strength	60.0	MPa	
Impact	Nominal Value	Unit	
Notched Izod Impact (Area)	60.0	kJ/m²	
Thermal	Nominal Value	Unit	
Deflection Temperature Under Load (0.45 MPa, Unannealed)	68.0	°C	
Flammability	Nominal Value		Test Method
Flame Rating (1.60 mm)	V-0		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

