Premier HD20053

High Density Polyethylene Premier Polymers, LLC.

Message:

Premier HD20053 is a high density polyethylene copolymer intended for use in a variety of injection molding applications. Meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact.

General Information			
Features	Copolymer		
	Food Contact Acceptable		
	High Density		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.953	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16	20	- /10	ACTNA D1220
kg)	20	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

