

# Daelim Po1y® PP-124T

Polypropylene

DAELIM INDUSTRIAL CO., LTD.

## Message:

Product Description:  
DAELIM POLY PP-124T is the polypropylene homopolymer manufactured by DAELIM under the license of MONTELL using the Spheripol process.  
DAELIM POLY PP-124T is a homopolymer particularly suitable for BOP(Tenter) film of general packaging, laminate, adhesive tapes.

General Information			
Features	Rigid, good		
	Highlight		
	Workability, good		
Uses	Films		
Agency Ratings	FDA Food Exposure, Not Rated		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.2	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	98		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	36.3	MPa	ASTM D638
Tensile Elongation (Yield)	12	%	ASTM D638
Flexural Modulus	1570	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	49	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	100	°C	ASTM D648
Vicat Softening Temperature	153	°C	ASTM D1525
Additional Information			

Accelerated oven aging, ASTM D-3012, in air (forced circulation), 150°C: 360 hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

