

NEUSoft™ 597 Ether 60

Thermoplastic Polyurethane Elastomer

NEU Specialty Engineered Materials

Message:

NEUSoft is a translucent polyether urethane based material with good elasticity, vibration dampening, abrasion and tear resistance. This series of polyurethanes are chemically resistant to hydrolysis and suitable for overmolding on polyolefins, ABS, PC, Pebax and nylon. NEUSoft 597-60 provides a good moisture and oxygen barrier as well as UV stability.

General Information			
Features	Excellent Elastic Recovery		
	Good Chemical Resistance		
	Good Flexibility		
	Good Melt Strength		
	Good Processability		
	Soft		
Uses	Medical/Healthcare Applications		
	Overmolding		
	Tubing		
Agency Ratings	ISO 10993 Part 4 1		
	ISO 10993 Part 5 1		
	USP Class VI		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.03	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	70		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.13	MPa	ASTM D412
Tensile Strength (Break)	25.7	MPa	ASTM D412
Tensile Elongation (Break)	730	%	ASTM D412
Tear Strength	50.4	kN/m	ASTM D624
Compression Set	38	%	ASTM D395

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHEG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

