

ESTYRENICS 416

High Impact Polystyrene

PCC Plastics & Consultations Center

Message:

ESTYRENICS 416 is a High Impact Polystyrene product. It is available in Africa & Middle East or Europe. Applications of ESTYRENICS 416 include containers, consumer goods, household applications and sheet. Primary characteristic: impact resistant.

General Information	
---------------------	--

Features	High Impact Resistance
Uses	Consumer Applications
	Containers
	Food Containers
	Household Goods
	Sheet

Physical	Nominal Value	Unit
----------	---------------	------

Density	1.04	g/cm ³
Melt Volume-Flow Rate (MVR)	22.0	cm ³ /10min

Mechanical	Nominal Value	Unit
------------	---------------	------

Tensile Modulus	2600	MPa
Tensile Strength (Break)	30.0	MPa
Tensile Elongation (Break)	35	%
Flexural Strength	46.0	MPa

Impact	Nominal Value	Unit
--------	---------------	------

Charpy Unnotched Impact Strength	5.0	kJ/m ²
----------------------------------	-----	-------------------

Thermal	Nominal Value	Unit
---------	---------------	------

Vicat Softening Temperature	80.0	°C
Deflection Temperature	71	°C
Residual Monomer	200	ppm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT