

TEREZ PA/PP 7200

Polyamide 6 + PP
TER HELL PLASTIC GMBH

Message:

High viscosity, impact modified special compound with good mechanical characteristics.
Suitable for high impact stress at low water absorption, for extrusion applications.

General Information			
Additive	Impact Modifier		
Features	High Impact Resistance		
	High Viscosity		
	Impact Modified		
	Low to No Water Absorption		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.05	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2500	MPa	ISO 527-2
Tensile Strain			ISO 527-2
Yield	5.0	%	
Break	7.0	%	
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	9.0	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT