Huafon JF-S-H8021

Polyurethane

Huafon Group Co., Ltd.

Message:

Heat-Resistance Type

Characteristics

Super soft type, good elasticity, good heat resistance, solvent resistance, swelling resistance, nonstick surface.

2.00 to 3.00

> 30.0

> 800

Applications

Garments, Shoes, Bags

General Information						
Features	High Elasticity Medium Heat Resistance Non-Stick Soft					
					Solvent Resistant	
				Uses	Bags	
Footwear						
Textile Applications						
Additional Information	Nominal Value	Unit				
Solvents	DMF/MEK					
Uncured Properties	Nominal Value	Unit				
Solids Content	29 to 31	%				
Viscosity (25°C)	80 to 140	Pa·s				
Cured Properties	Nominal Value	Unit				

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

MPa

MPa

%

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Tensile Modulus (100% Secant)

Tensile Elongation at Break

Tensile Strength

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

