

SQUARE® LSG6933-20A/B

Silicone Rubber, LSR
Shenzhen SQUARE Silicone Co., Ltd.

Message:

Addition type electronic encapsulation silicone gel for PCB

Product description

The product is one kind of 2-part additional type liquid silicone rubber, catalyzed by platinum, mixing ratio of parts A:B=1:1, cured under room temperature or heat cure under low temperature.

Key Features

Good light transmittance, non-toxic and eco-friendly.

Application

Electronic encapsulation silicone gel for PCB

General Information			
Features	High Light Transmission		
	Environmental protection		
	Heat vulcanization		
	Room temperature vulcanization		
	Non-toxic		
Uses	Encapsulant		
	Electrical/Electronic Applications		
	Printed circuit board		
Appearance	Clear/transparent		
Processing Method	Enclosure		
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Component a	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by weight: 1.0		
Shelf Life	52	wk	
Uncured Properties	Nominal Value	Unit	Test Method
Viscosity	2.0	Pa·s	DIN 53019

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

