

# Sylvin 8339-70FUV White 1522

Rigid Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:

Sylvin 8339-70FUV White 1522 Is A Vinyl Compound Formulated For Co Extrusion With Rigid. This Compound Contains An Antimicrobial And An Ultra Violet Stabilizer.

General Information			
Additive	Antimicrobial (Fungicide)		
	UV Stabilizer		
Features	Good UV Resistance		
	High Rigidity		
	Microbe Resistant		
Appearance	White		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	14.5	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	52.5	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	160 to 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT