

LightSpan® LS-3249

Silicone

NuSil Technology

Message:

From LEDs to fiber optics, NuSil Technology's LightSpan™ brand product line delivers the most comprehensive line of refractive index matching adhesives, encapsulants and thermosets available.

The benefits of silicone include the following:

Thermal Stability

Low Ionic Species

Maintain Optical Clarity (90% minimum @ 400nm)

Low Moisture Absorption (<0.4%)

Optimization for UV Resistance

Adjustable Cure

Low Outgassing

Low Shrinkage, <1%

Low Modulus: Stress reduction for bonding materials with different coefficients of thermal expansion

Gernal Purpose: Optical Gels

Comments: Index matches to acrylates such as PMMA

General Information		
Features	Good Thermal Stability	
	Good UV Resistance	
	Low Moisture Absorption	
	Low Shrinkage	
	Low to No Outgassing	
Forms	Gel	
Processing Method	Encapsulating	
Optical	Nominal Value	
Refractive Index	1.490	
Thermoset	Nominal Value	Unit
Thermoset Components		
Part A	Mix Ratio by Weight: 1.0	
Part B	Mix Ratio by Weight: 1.0	
Uncured Properties	Nominal Value	Unit
Curing Time (75°C)	1.0	hr
Pot Life	2900	min
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore OO)	60	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

