

NEXUS PE LLDPE-5024

Linear Low Density Polyethylene

Nexus Resin Group, LLC.

Message:

Linear Low Density Polyethylene for compounding and injection molding
Nexus LLDPE-5024 is designed for compounding and injection molding applications requiring excellent processability.

General Information			
Features	Good Processability		
Uses	Compounding		
Processing Method	Compounding		
	Injection Molding		

Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	50	g/10 min	ASTM D1238

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	7.58	MPa	ASTM D638
Tensile Elongation (Break)	90	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT