Moplen EP336J

Polypropylene Impact Copolymer LyondellBasell Industries

Message:

Moplen EP336J is the polypropylene block copolymer manufactured by PMC under the license of BASELL using the Spheripol process. Moplen EP336J is a block copolymer selected by customers for use in injection molding of Toy, Crates.

Moplen EP336J resin meets the FDA requirements in the Code of Federal Regulations in 21 CFR 177.1520 for food contact.

General Information					
Features	Block Copolymer				
	Low warpage				
	Rigidity, high				
	Rigid, good				
	Impact resistance, high				
	Low temperature impact resistance				
	Good toughness				
	Compliance of Food Exposure				
Uses	Household goods				
	Toys				
	Loading box				
	J				
Agency Ratings	FDA 21 CFR 177.1520				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	3.0	g/10 min	ASTM D1238		
Hardness	Nominal Value Unit		Test Method		
Rockwell Hardness (R-Scale, Injection Molded)	86		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield, Injection Molded)	24.5	MPa	ASTM D638		
Tensile Elongation (Yield, Injection					
Molded)	7.0	%	ASTM D638		
Flexural Modulus (Injection Molded)	1180	МРа	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C, injection molding	59	J/m	ASTM D256		
23°C, injection molding	440	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		

Deflection Temperature Under Load (0.45					
MPa, Unannealed, Injection Molded)	96.0	°C	ASTM D648		
Vicat Softening Temperature	147	°C	ASTM D1525		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

