ADEKA EP-4000

Epoxy; Epoxide

Adeka Corporation

Message:

Flexibility

Civil engineering, adhesion, electrics

| General Information | | | |
|---------------------|------------------------------------|--|--|
| Features | Good Adhesion | | |
| | Good Flexibility | | |
| | | | |
| Uses | Adhesives | | |
| | Electrical/Electronic Applications | | |
| | Engineered Applications | | |
| | | | |
| Physical | Nominal Value Unit | | |

| Physical | Nominal Value | Unit | |
|--------------------------------|---------------|-------|--|
| Specific Gravity | 1.14 | g/cm³ | |
| Color - G, Max | 1.0 | | |
| Epoxy Equivalent | 320 g/ep | | |
| Thermoset | Nominal Value | Unit | |
| Thermoset Mix Viscosity (25°C) | 4500 | сР | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

