Extir® CM Galileo Europa 5 AE

Expanded Polystyrene

Versalis S.p.A.

Message:

Extir CM is the new range of expandable products produced using Continuous Mass technology. All the products have a very low dimensional dispersion and a reduced content of blowing agent. Extir CM does not contain CFC or HCFC.

Extir CM Galileo Europa 5 AE contains an atherman additive that reduces heat transfer and the items produced with it, grey in colour, have excellent thermal insulation properties. Its particular formula permits the use of thinner boards to get the same thermal resistance.

Applications

Extir CM Galileo Europa 5 AE achieves optimum thermal insulation performance. It is therefore recommended for all applications in which thickness is a limiting factor:

cavity wall insulation

floor insulating boards

General Information			
Additive	Blowing Agent		
	Flame Retardant		
	Heat Stabilizer		
Features	Expandable		
	Flame Retardant		
	Good Surface Finish		
	Low Shrinkage		
	Thermally Insulating		
Uses	Flooring		
	Insulation		
Agency Ratings	DIN 4102/B1		
Appearance	Grey		
Physical	Nominal Value	Unit	
Density	0.0120 to 0.0250	g/cm³	
Apparent Density			
1	0.01	g/cm³	
2	0.02	g/cm³	
	0.59 to 0.63	g/cm³	
Particle Size	0.900 to 1.60	mm	
NOTE			
1	on a continuous pre-expander		
1.	after two expansions		
2.	on a discontinuous pre-expander		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2