

Comai 664-3 BL

Linear Low Density Polyethylene

Comai Ltda

Message:

Comai 664-3 BL is a Linear Low Density Polyethylene product filled with 30% calcium carbonate. It can be processed by injection blow molding and is available in Latin America. Applications of Comai 664-3 BL include additive/masterbatch, bags/liners and packaging.

General Information			
Filler / Reinforcement	Calcium Carbonate,30% Filler by Weight		
Additive	Titanium Dioxide (TiO2) (40%)		
Uses	Bags		
	Packaging		
	Plastics Modification		
Forms	Pellets		
Processing Method	Injection Blow Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	20	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

