

SolVin 550GA

Polyvinyl Chloride Copolymer
INOVYN

Message:

Polyvinyl chloride copolymer made by suspension polymerisation.

APPLICATIONS

Flooring.
Inks and glue.

PROCESSING TECHNIQUES

Calendering.

General Information			
Features	Copolymer		
	Suspension Polymers		
Uses	Adhesives		
	Flooring Maintenance/Repair		
Forms	Pellets		
Processing Method	Calendering		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.53	g/cm ³	ISO 60
K-Value	50.0		ISO 1628-2
Vinyl Acetate Content	13.0	wt%	Internal Method
Sieve Analysis			ISO 1624
-- 1	> 40	%	
-- 2	< 1.5	%	
Volatile Matter	< 0.30	%	ISO 1269
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 24538
NOTE			
1.	Retained on 0.063 mm sieve		
2.	Retained on 0.180 mm sieve		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT