

Sinvicomp SGH6040

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SGH6040 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp SGH6040: Good Stiffness.

Typical application of Sinvicomp SGH6040: Hose/Tubing

General Information			
Features	Good Stiffness		
Uses	Garden Hose		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.38	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness	73		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	16.2	MPa	ASTM D638
Tensile Elongation (Break)	320	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT