

ARCEL® 640 (1.85 pcf)

Polystyrene + PE
NOVA Chemicals

Message:

ARCEL® 640 (1.85 pcf) is a Polystyrene + PE (PS+PE) material. It is available in North America for foam processing.
Typical application of ARCEL® 640 (1.85 pcf): Foam

General Information			
Features	Expandable		
Uses	Foam		
Appearance	White		
Forms	Spheres		
Processing Method	Foam Processing		
Physical	Nominal Value	Unit	
Density	0.0296	g/cm ³	
Particle Size - 98%	0.700 to 1.40	mm	
VOC Content			
Pentane	9.2	%	
Plasticizer	0.30	%	
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength (5.0% Strain)	0.332	MPa	ASTM C203
Compressive Strength			ASTM D1621
25% Strain	0.171	MPa	
50% Strain	0.187	MPa	
75% Strain	0.225	MPa	
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	0.498	MPa	ASTM D412
Tensile Elongation (Break)	12	%	ASTM D412
Flammability	Nominal Value	Unit	Test Method
Burning Rate	73	mm/min	FMVSS 302

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT