

# FRABUR 63 A

Polyolefin

Crosspolimeri S.p.A.

## Message:

FRABUR is the trade-mark of our flame retardant halogen free polyolefine thermoplastic compounds suitable for fillers.  
FRABUR 63 A is a general purpose flame retardant filling compound, easy to process with high LOI.

General Information			
Features	Flame Retardant		
	General Purpose		
	Good Processability		
	Halogen Free		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.80	g/cm <sup>3</sup>	ASTM D792
Viscosity - ML (1+4 a 100°C)	40.0		ASTM D1646
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	> 50	%	ASTM D2863
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	60.0	°C	
Cylinder Zone 2 Temp.	70.0	°C	
Cylinder Zone 3 Temp.	80.0	°C	
Cylinder Zone 4 Temp.	90.0	°C	
Cylinder Zone 5 Temp.	100	°C	
Die Temperature	100	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT