

# Melthene® -H H6410M

Ethylene Vinyl Acetate Copolymer

TOSOH Corporation

## Message:

Melthene® -H H6410M is an Ethylene Vinyl Acetate Copolymer (EVA) material. It is available in Asia Pacific, Europe, or North America for coextrusion.

Important attributes of Melthene® -H H6410M are:

Chemical Resistant

Copolymer

Good Adhesion

Good Weather Resistance

Typical application of Melthene® -H H6410M: Wire & Cable

General Information			
Features	Copolymer		
	Good Adhesion		
	Good Weather Resistance		
	Solvent Resistant		
Uses	Wire & Cable Applications		
Forms	Pellets		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm <sup>3</sup>	ASTM D1505
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	87.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

