

EVERLON® TSO-80

Styrene Ethylene Butylene Styrene Block Copolymer + EPDM

Ever Polymer Co., Ltd.

Message:

Dry-touch and heat-resistant grade.

Base on EPDM/ SEBS, to replace the traditional rubber.

General Information			
Features	High Heat Resistance		
Uses	Rubber Replacement		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.948	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength	8.83	MPa	ASTM D412
Tensile Elongation (Break)	480	%	ASTM D412
Tear Strength	58.8	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-40.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT