

NEXT REGRIND POMC M90-300RG

Acetal (POM) Copolymer
NEXT Specialty Resins, Inc.

Message:

NEXT REGRIND POMC M90-300RG is an Acetal (POM) Copolymer material. It is available in North America for injection molding.
Important attributes of NEXT REGRIND POMC M90-300RG are:
Eco-Friendly/Green
Copolymer
Good Processability
Typical application of NEXT REGRIND POMC M90-300RG: Automotive

General Information			
Recycled Content	Yes		
Features	Copolymer		
	General Purpose		
	Good Moldability		
Uses	Automotive Applications		
Appearance	Black		
Forms	Regrind		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.40	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	10 to 12	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	80		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2520	MPa	ASTM D790
Tensile Strength	58.6	MPa	ASTM D638
Tensile Elongation (Break)	58	%	ASTM D638
Flexural Modulus	2550	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	61	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	107	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

