

# Kumho EPS GN16

Expanded Polystyrene

Korea Kumho Petrochemical Co., Ltd.

Message:

Features: General

Applications: Buoy, Packing materials

General Information			
Features	General Purpose		
Uses	General Purpose		
	Packaging		
Physical	Nominal Value	Unit	Test Method
Density	0.0200	g/cm <sup>3</sup>	Internal Method
Water Absorption	0.400	g/100 cm <sup>2</sup>	Internal Method
Molded Density	15.0 to 18.0	kg/m <sup>3</sup>	Internal Method
Compressive Strength	0.0900	MPa	Internal Method
Bead Size	0.900 to 1.10	mm	Internal Method
Blowing Agent	5.0	%	Internal Method
Flexural Demolition Load	26	N	Internal Method
Optimum Expansion Multiple	75.0		Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT