## Delta ATL C9-SG

## Acetal (POM) Copolymer

## **Delta Polymers**

## Message:

Delta ATL C9-SG is an Acetal (POM) Copolymer product. It is available in North America. Typical application: Food Contact Applications. Primary characteristic: flame rated.

General Information			
Agency Ratings	FDA 21 CFR 177.2470 (a)		
	FDA 21 CFR 177.2470 (b)		
	FDA 21 CFR 177.2470 (c)		
	FDA 21 CFR 177.2470 (d) (2)		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)	9.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.8 to 2.2	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	62.1	MPa	ASTM D638
Tensile Elongation (Break)	60	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	69	J/m	ASTM D256
Thermal	Nominal Value	Unit	

Melting Temperature165°CFlammabilityNominal ValueTest MethodFlame RatingHBUL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

