

MTEGRITY™ HDPE HD360

High Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ HDPE HD360 is a High Density Polyethylene product. It can be processed by injection molding and is available in North America. Typical application: Containers.

Characteristics include:

High Stiffness

Homopolymer

General Information			
Features	High Stiffness		
	Homopolymer		
Uses	Crates		
	Tool/Tote Box		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.962	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	29.3	MPa	ASTM D638
Tensile Elongation (Break)	900	%	ASTM D638
Flexural Modulus	1380	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT