

Hostacom M2 V17

Polypropylene Copolymer

LyondellBasell Industries

Message:

"Hostacom" M2 V17 is a high melt flow polypropylene copolymer for injection moulding. The grade has high stiffness and is formulated with UV stabilisers suitable for exterior applications.

The grade is available in custom colour, pellet form.

General Information			
Additive	UV Stabilizer		
Features	Copolymer		
	Good Dimensional Stability		
	Good UV Resistance		
	High Flow		
	High Rigidity		
	High Stiffness		
	Medium Impact Resistance		
Uses	Automotive Applications		
	Outdoor Applications		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.07	g/cm³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	25	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	25.0	MPa	ISO 527-2/50
Flexural Modulus - Secant	2200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	4.5	kJ/m²	ISO 180/1A
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	65.0	°C	ISO 75-2/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

