

Huaфон JF-S-PV8150

Polyurethane

Huaфон Group Co., Ltd.

Message:

Semi-PU Type

Characteristics

Hard type, good adhesive strength with PVC, abrasion resistance, solvent resistance, heat resistance, DOP resistance.

Applications

Semi-Pu

General Information		
Features	Good Abrasion Resistance	
	Good Adhesion	
	High Hardness	
	Medium Heat Resistance	
	Solvent Resistant	
Additional Information	Nominal Value	Unit
Solvents	DMF/MEK	
Uncured Properties	Nominal Value	Unit
Solids Content	29 to 31	%
Viscosity (25°C)	80 to 140	Pa·s
Cured Properties	Nominal Value	Unit
Tensile Modulus (100% Secant)	14.0 to 16.0	MPa
Tensile Strength	> 45.0	MPa
Tensile Elongation at Break	> 300	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

