

Exelene® PVC K65

Polyvinyl Chloride Homopolymer

Montachem International, Inc.

Message:

Applications:

Irrigation Pipe, Potable Water Supply Pipe, Rigid Profiles

Characteristics:

Exelene PVC K65 is typically used in rigid PVC compounds which can be processed through both single and multi screw extrusion of pipe and conduit

General Information	
Features	Homopolymer
Uses	Irrigation Applications Piping Potable Water Applications Profiles
Processing Method	Extrusion Pipe Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.40	g/cm ³	ASTM D792
Apparent Density	0.56	g/cm ³	ASTM D1895
K-Value	65.0		DIN 53726
Inherent Viscosity	0.90		ASTM D1243
Particle Size			
200 Mesh	< 4.00	%	
40 Mesh	< 99.0	%	
Relative Viscosity	2.16		
Volatiles	< 0.30	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT