

Quantum Composites QC-8816

Vinyl Ester

Quantum Composites Inc.

Message:

QC-8816 is an ESC molding compound reinforced with continuous, unidirectional (0°) glass fibers. It provides high strength, stiffness, and fatigue resistance in the fiber direction, and can be used to selectively reinforce other materials.

General Information			
Filler / Reinforcement	Glass Fabric,66% Filler by Weight		
Features	Fatigue Resistant		
	High Stiffness		
	High Strength		
Appearance	Black		
Forms	SMC - Sheet Molding Compound		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.95	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Barcol Hardness	68		ASTM D2583
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	621	MPa	ASTM D638
Flexural Modulus	41400	MPa	ASTM D790
Flexural Strength	1100	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	3700	J/m	ASTM D256
Thermoset	Nominal Value	Unit	
Shelf Life (24°C)	8.7	wk	
Post Cure Time (138°C)	0.050 to 0.083	hr	
Injection	Nominal Value	Unit	
Mold Temperature	132 to 149	°C	
Injection Pressure	2.07 to 6.89	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

