Huaxia Shenzhou FKM DS2601-2

Fluoroelastomer

Shandong Huaxia Shenzhou New Material Co., Ltd.

Message:

Fluorous rubber (FKM-DS2600), commonly called 2# rubber, is white elastomer and copolymer of VDF and hexafluoropropylene, with fluorine content of over 66%. The product processed and vulcanized by raw fluorous rubber (DS2600), featured by good mechanical property and excellent oil resistance (fuels, synthetic oils, lubricating oils) and heat resistance, is an indispensable material for modern aviation, rocket, missile, space flight, and other top technologies and industries.

Characteristic: Low Mooney viscosity, good polymer rheological properties

Application: Additives for reducing the viscosity of high Mooney rubber, O-rings, and anti-extrusion parts of synthetic products

General Information					
Features	Copolymer				
	Fuel Resistant				
	Good Corrosion Resistance				
	Good Weather Resistance				
	High Heat Resistance				
	Low Viscosity				
	Oil Resistant				
	Ozone Resistant				
	Radiation (Gamma) Resistant				
Uses	Additive				
	Aerospace Applications				
	Cable Jacketing				
	Coating Applications				
	Diaphragms				
	Gaskets				
	Piping				
	Seals				
Appearance	Transparent - Slight Yellow				
	White				
Forms	Film				
Physical	Nominal Value	Unit			
Specific Gravity	1.78 to 1.83	g/cm³			
Mooney Viscosity (ML 1+10, 121°C)	30 to 39	MU			
Elastomers	Nominal Value	Unit			
Tensile Strength					
	> 11.0	MPa			
1	> 9.00	MPa			

Tensile Elongation				
Break	> 150	%		
Break ²	> 120	%		
Compression Set ³ (200°C, 24 hr)	< 25	%		
NOTE				
1.	Aged for 24 hr at 275°C			
2.	Aged for 24 hr at 275°C			
	Bisphenol AF, compression	ratio		
3.	30%			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

