

Alkathene® LD1217

Linear Low Density Polyethylene

Qenos Pty Ltd

Message:

LD1217 is an extrusion coating grade exhibiting very low odour and taint and excellent heat seal characteristics. It also has good drawdown and very low neck-in allowing low coating weights whilst maintaining very good adhesion to a variety of substances. Ideally suited for liquid packaging and other sensitive food packaging laminates.

General Information			
Features	Food Contact Acceptable		
	Good Adhesion		
	Good Drawdown		
	Good Heat Seal		
	Heat Sealable		
	Low Neck-In		
	Low to No Odor		
Uses	Coating Applications		
	Food Packaging		
	Packaging		
Agency Ratings	AS 2070-1999 4.1.1(a)		
	FDA 21 CFR 177.1520(c) 2.1		
Forms	Pellets		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.918	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	12	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	85.0	°C	ASTM D1525
Peak Melting Temperature	106	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

