RTP 700 GB 20

High Density Polyethylene RTP Company

Message:

Warning: The status of this material is 'Commercial: Limited Issue'
The data for this material has not been recently verified.

Please contact RTP Company for current information prior to specifying this grade.

General Information			
Filler / Reinforcement	Glass beads, 20% filler by weight		
Features	High density		
RoHS Compliance	Contact manufacturer		
Appearance	Black		
	Natural color		
	D. C. I.		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.07	g/cm³	ASTM D792
Molding Shrinkage - Flow (3.18 mm, Injection Molded)	1.8 - 2.2	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (Injection Molded)	1520	MPa	ASTM D638
Tensile Strength	18.0	MPa	ASTM D638
Tensile Elongation (Yield, Injection	10	07	ACTAA DC20
Molded)	10	%	ASTM D638
Flexural Modulus (Injection Molded)	1030	MPa	ASTM D790
Flexural Strength (Injection Molded)	23.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (3.18 mm, Injection Molded)	69	J/m	ASTM D256
Unnotched Izod Impact (3.18 mm)	1300	J/m	ASTM D4812
Flammability	Nominal Value		Test Method
Flame Rating (1.50 mm)	НВ		UL 94
Additional Information			
The value listed as Flammibility, UL 94, was t	ested in accordance with RTP Com	pany methods.	
Injection	Nominal Value	Unit	
Rear Temperature	177 - 227	°C	
Middle Temperature	177 - 227	°C	
Front Temperature	177 - 227	°C	
Mold Temperature	21.0 - 66.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

