

Niuk YPC4008

Acetal (POM) Copolymer

Shanghai Niuk New Plastic Technology Co., Ltd.

Message:

Niuk YPC4008 is an Acetal (POM) Copolymer material filled with 15% glass fiber. It is available in Asia Pacific. Primary attribute of Niuk YPC4008: Flame Rated.

General Information			
Filler / Reinforcement	Glass Fiber,15% Filler by Weight		
Physical	Nominal Value	Unit	Test Method
Density	1.51	g/cm ³	ISO 1183
Molding Shrinkage	0.60 to 1.0	%	ISO 2577
Ash Content	15	%	ISO 3451
Heat Deflection Temperature	157	°C	ISO 75-2
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	80.0	MPa	ISO 527-2
Tensile Strain (Break)	2.0 to 5.0	%	ISO 527-2
Flexural Modulus	5000	MPa	ISO 178
Flexural Stress	100	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	60	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ISO 306
Flammability	Nominal Value	Test Method	
Flame Rating	HB	UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

