

HYBRANCH HP-100F-2

Specialty Polystyrene

DIC Corporation

Message:

HYBRANCH HP-100F-2 is a Specialty Polystyrene product. It can be processed by extrusion and is available in Asia Pacific or North America. Applications of HYBRANCH HP-100F-2 include film and sheet. Primary characteristic: high strength.

General Information			
Features	High Strength		
Uses	Film		
	Sheet		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.04 to 1.05	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR)	1.5	g/10 min	ISO 1133
Molding Shrinkage	0.40 to 0.80	%	ISO 294-4
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	68		ISO 2039-2
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	56.0	MPa	ISO 527-2
Tensile Strain (Break)	2.0	%	ISO 527-2
Flexural Modulus	3300	MPa	ISO 178
Flexural Stress	105	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	2.5	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	96.0	°C	ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT