

# NuSil R-2560

Silicone

NuSil Technology

Message:

The Aircraft Industry has used silicone adhesives and coatings for over five decades. Silicone's ability to maintain its elasticity and low modulus over a broad temperature range provides excellent utility in extreme environments. Recent advances in material technology provide more opportunities for the Aircraft engineer in choosing the best material for an intended application. Examples of NuSil's capabilities in custom silicones for Aircraft are demonstrated in the following sections.

- Fuel Resistance
- Static Dissipation and Electrically Conductive Silicones
- Ice-Phobic Coatings
- General Purpose: Adhesives and Sealants
- Comment: High Temperature Elastomer

General Information		
Features	Electrically Conductive	
	Fuel Resistant	
	High Heat Resistance	
Uses	Adhesives	
	Aircraft Applications	
	Sealants	
Thermoset	Nominal Value	Unit
Thermoset Components		
Part A	Mix Ratio by Weight: 100	
Part B	Mix Ratio by Weight: 0.50	
Additional Information	Nominal Value	Unit
Cure System	Tin	
Operating Temperature	-115 to 200	°C
Uncured Properties	Nominal Value	Unit
Color	Red	
Density	1.41	g/cm <sup>3</sup>
Viscosity	31	Pa · s
Curing Time (23°C)	1.7E+2	hr
Pot Life	120	min
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore A)	55	
Lap Shear Strength <sup>1</sup>	2.65	MPa
Tensile Strength	4.83	MPa
Tensile Elongation at Break	130	%
NOTE		
1.	Primed with SP-130	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

