

Sylvin 9302-70 FU BROWN 7251

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 9302-70 FU Brown 7251 Is A Vinyl Compound Formulated For Co-extrusion Applications Where Outdoor Weathering And A Antimicrobial Are Needed.

General Information	
Additive	Antibacterial (fungicide)
Features	Good weather resistance
Uses	Building materials
	Architectural application field
Appearance	Brown
Processing Method	Co-extrusion molding
	Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	70		ASTM D2240
Shaw A, 10 seconds	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	14.1	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	47.3	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	160 - 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT