

Fixmaster Elast. Corrosion Coating

Polyurethane

Loctite®

Message:

Fixmaster Elast. Corrosion Coating is a Polyurethane product. It is available in North America. Typical application: Coating Applications.

Characteristics include:

Chemical Resistant

Corrosion Resistant

Good Adhesion

Good Weather Resistance

Heat Resistant

General Information			
Features	Bondability		
	Good Abrasion Resistance		
	Good Corrosion Resistance		
	Good Impact Resistance		
	Good Thermal Stability		
	Good Weather Resistance		
	Grease Resistant		
	High Gloss		
	Oil Resistant		
Uses	Protective Coatings		
Appearance	Red		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	13.8	MPa	ASTM D638
Tensile Elongation (Yield)	250	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	10 to 15	min	
Demold Time (25°C)	360 to 480	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

