

# Sinvicomp SRP8602

Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

## Message:

Sinvicomp SRP8602 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp SRP8602: Impact Resistant.

Typical applications include:

Electrical/Electronic Applications

Plumbing/Piping/Potable Water

General Information			
Features	Good Impact Resistance		
Uses	Conduit		
	Piping		
	Profiles		
Forms	Granules		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.42	g/cm <sup>3</sup>	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Yield)	50.0	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Break)	160	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	29	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	96.0	°C	ASTM D1525
Thermal Stability <sup>3</sup> (190°C)	> 1	hr	BS 2782
NOTE			
1.	250 mm/min		
2.	250 mm/min		
3.	Congo Red		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

