

Europrene Latice® CC 136

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Latice CC 136 is an aqueous dispersion of a modified carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers.

Main Applications

Europrene Latice CC 136 is used for offset paper and board coating.

General Information			
Features	Copolymer		
Uses	Coating Applications		
	Paper Coatings		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
pH	7.0		ASTM D1417
Solids Content	50.0	wt%	ASTM D1417
Surface Tension	38	mN/m	ASTM D1417
Brookfield Viscosity ¹ (25°C)	300	mPa·s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

