NuSil MED1-6300

Silicone

NuSil Technology

Message:

1.

NuSil Technology's unrestricted materials may be considered for long-term implant applications (greater than 29 days).

A silicone gel is an unreinforced, loosely crosslinked network of polymers. Due to the lack of reinforcing fi ller, gels tend to be low in viscosity in the uncured state, allowing fl exibility for various processing techniques. Not only can the crosslink density of the silicone polymers be designed to yield a very fi rm or soft gel, but the work time and cure profi le can also be modifi ed. Accordingly, gels can be used in a variety of applications, including sheeting and encapsulating sensors or electronic devices.

Comments: HIGH PURITY, HIGH PENETRATION, SOFT COHESIVE GEL

General Information				
Features	Biocompatible Breathable High Purity Low Viscosity			
			Soft	
	Uses	Electrical/Electronic Applications		
Medical/Healthcare Applications				
Agency Ratings	USP Class VI			
Forms	Gel			
Processing Method	Encapsulating			
Thermoset	Nominal Value	Unit		
Thermoset Components				
Part A	Mix Ratio by Weight: 1.0			
Part B	Mix Ratio by Weight: 1.0			
Additional Information	Nominal Value	Unit		
Cure System	Platinum			
Penetration Depth ¹	5.00	mm		
Uncured Properties	Nominal Value	Unit		
Density	0.978	g/cm³		
Viscosity	1.0	Pa·s		
Curing Time (140°C)	5.0	hr		
NOTE				
	Shaft weight/foot diameter/	time ·		

Shaft weight/foot diameter/time :

12g/25.4mm/15s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

