

CONAP® AD-6407

Polyurethane

Cytec Industries Inc.

Message:

CONAP AD-6407 is a two-component thixotropic urethane system designed for use as a sealant.

General Information		
Features	Thixotropic	
Uses	Sealants	
Appearance	Amber	
Physical	Nominal Value	Unit
Specific Gravity		
-- ¹	0.980	g/cm ³
-- ²	1.14	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	70	
Elastomers	Nominal Value	Unit
Tensile Strength	22.8	MPa
Tensile Elongation (Break)	72	%
Tear Strength	85.8	kN/m
Thermoset	Nominal Value	Unit
Thermoset Components		
Hardener	Mix Ratio by Weight: 88	
Resin	Mix Ratio by Weight: 100	
Thermoset Mix Viscosity ³ (25°C)	45000	cP
NOTE		
1.	Hardener	
2.	Resin	
3.	(SP 7 @ 10 RPM)	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT