

Hanwha Total PE R908U

High Density Polyethylene
HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:
R908U resin is in pellet form and is a linear low density polyethylene designed for rotational molding application.

General Information			
Additive	UV Stabilizer		
Features	Good Chemical Resistance		
	Good Flow		
	Good Processability		
	Good UV Resistance		
	High ESCR (Stress Crack Resist.)		
	High Impact Resistance		
	High Rigidity		
	Low Density		
Uses	Oil Resistant		
	Outdoor Applications		
	Tanks		
Agency Ratings	Toys		
	FDA 21 CFR 177.1520		
	Pellets		
Forms	Rotational Molding		
Processing Method			
Physical	Nominal Value	Unit	Test Method
Density	0.940	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.4	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	1000	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	63		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	19.0	MPa	
Break	22.0	MPa	
Tensile Elongation (Break)	1000	%	ASTM D638
Apparent Bending Modulus	770	MPa	ASTM D747
Impact	Nominal Value	Unit	Test Method

Notched Izod Impact	390	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	118	°C	ASTM D1525 ¹
NOTE			
1.	Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT