

# SAPYLENE T30HEB

Polypropylene  
Sahel Chimie Co.

Message:

SAPYLENE T30HEB is a Polypropylene material filled with 30% talc. It is available in Africa & Middle East. Primary attribute of SAPYLENE T30HEB: Non-Toxic.  
Typical applications include:  
Automotive  
Industrial Applications

General Information			
Filler / Reinforcement	Talc,30% Filler by Weight		
Features	Non-Toxic		
Uses	Automotive Applications		
	Industrial Applications		

Physical	Nominal Value	Unit	Test Method
Density	1.14	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	9.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 23°C)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2/100
Yield	12.5	MPa	
Break	2.34	MPa	
Tensile Strain (Break)	5.3	%	ISO 527-2/100
Flexural Modulus <sup>1</sup>	2.14	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact <sup>2</sup> (23°C)	7.0	J/m	ISO 180
NOTE			
1.	100 mm/min		
2.	1A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

