

Ablebond 7501F

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablebond 7501F is an Epoxy; Epoxide (Epoxy) material. It is available in North America for encapsulating. Primary attribute of Ablebond 7501F: High Purity.
Typical application of Ablebond 7501F: Coating Applications

General Information			
Features	High Purity		
Uses	Coating Applications		
Forms	Pellets		
Processing Method	Encapsulating		
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	10300	MPa	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	170	°C	ASTM E1356
Thermoset	Nominal Value	Unit	
Pot Life	2900	min	
Shelf Life (-40°C)	52	wk	
Demold Time (150°C)	60	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT