

Sinvicomp SSN6028A

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SSN6028A is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.

Important attributes of Sinvicomp SSN6028A are:

Chemical Resistant

Wear Resistant

Typical application of Sinvicomp SSN6028A: Wire & Cable

General Information			
Features	Good Abrasion Resistance		
	Good Chemical Resistance		
Uses	Wire & Cable Applications		
Wire Types	5V-90		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.31	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	73		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	20.0	MPa	IEC 811-1-1
Tensile Elongation ¹ (Break)	380	%	IEC 811-1-1
Aging	Nominal Value	Unit	Test Method
Change in Tensile Strength (115°C, 504 hr)	25	%	AS 3147/3191
Change in Ultimate Elongation (115°C, 504 hr)	35	%	AS 3147/3191
NOTE			
1.	250 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT