# ELASTOSIL® RT 646 A/B

#### Silicone

## Wacker Chemie AG

#### Message:

Silicone Rubber, RTV-2 all-round potting compounds, Lighting all-round potting compounds, Electrical Industry all-round potting compounds, Automotive & Transportation Potting Compound, Electronics Potting Compound, Automotive & Transportation

General Information	
Uses	Electrical/Electronic Applications
Processing Method	Encapsulating
	Potting

Uncured Properties	Nominal Value	Unit	Test Method
Color	Beige		
Density	1.28	g/cm³	ISO 2781
Viscosity	70	Pa·s	ISO 3219
Pot Life	80	min	
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	53		ISO 868
Tensile Strength	5.00	MPa	ISO 37
Tensile Elongation at Break	280	%	ISO 37
Tear Strength	12.0	kN/m	ASTM D624B
Linear Shrinkage	< 0.10	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

