

Dugdale PVC Rigid Extrusion Black Compound

Rigid Polyvinyl Chloride

Dugdale Plc

Message:

A calcium/zinc stabilised, medium impact, satin finish extrusion compound.

This compound may be used for a variety of general-purpose applications, and being calcium/zinc stabilised is both RoHS and WEEE compliant.

Black in this case, but the same base can be supplied in other opaque colours matched to the customer's requirement.

General Information			
Additive	Calcium-Zinc Stabilizer		
Features	Good Impact Resistance		
	Good Stability		
	Good Surface Finish		
	High Rigidity		
Uses	General Purpose		
RoHS Compliance	RoHS Compliant		
Appearance	Black		
	Colors Available		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm ³	BS 2782 620A
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	40.0	MPa	BS 2782 320A-F
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	79.0	°C	BS 2782 120B ¹
NOTE			

1. Rate B (120°C/h), Loading 2 (50 N)

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT