

Sinvicomp DBS5906

Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp DBS5906 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp DBS5906: Impact Resistant.

Typical application of Sinvicomp DBS5906: Plumbing/Piping/Potable Water

General Information			
Features	Medium Impact Resistance		
Uses	Piping		
Forms	Powder		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.44	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	45.0	MPa	ASTM D638
Tensile Elongation ² (Break)	110	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	160	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	94.0	°C	ASTM D1525
NOTE			
1.	250 mm/min		
2.	250 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

