

Generic PUR-TDI

Polyurethane (TDI)

Generic

Message:

This data represents typical values that have been calculated from all products classified as: Generic PUR-TDI
This information is provided for comparative purposes only.

General Information			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.01 to 1.21	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (23°C)	79 to 91		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield, 23°C)	1.38 to 24.1	MPa	ASTM D412
Tensile Elongation (Break, 23°C)	580 to 700	%	ASTM D412
Thermoset	Nominal Value	Unit	Test Method
Pot Life (23°C)	1.8 to 40	min	
Thermoset Mix Viscosity	30.0 to 4070	cP	ASTM D2393
Demold Time	2.0 to 1000	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT