Rotuba CAB B900 (13% Plasticizer)

Cellulose Acetate Butyrate

Rotuba Extruders, Inc.

Message:

Rotuba CAB B900 (13% Plasticizer) is a cellulose acetate butyrate (CAB) product. It can be processed by injection molding and is available in North America. Rotuba CAB B900 (Plasticizer 13%) has applications including optics/lenses, automotive industry, commercial/office supplies, consumer goods and handles. Features include: environmental protection/green Good dimensional stability Impact resistance good weather resistance

General Information					
Features	Good dimensional stability				
	Updatable resources				
	Low temperature impact resistance				
	Good weather resistance				
	amorphous				
Uses	Handle				
	Optical applications				
	Application in Automobile Field				
	Toys				
	Stationery				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.18	g/cm³	ASTM D792		
Molding Shrinkage - Flow	0.20 - 0.60	%	ASTM D955		
Water Absorption (24 hr)	1.4	%	ASTM D570		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength			ASTM D638		
Yield	24.8	MPa	ASTM D638		
Fracture	34.5	MPa	ASTM D638		
Tensile Elongation (Break)	30	%	ASTM D638		
Flexural Modulus	1100	MPa	ASTM D790		
Flexural Strength	32.8	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	370	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		

Deflection Temperature Under Load (1.8				
MPa, Unannealed)	68.9	°C	ASTM D648	
Vicat Softening Temperature	100	°C	ASTM D1525	
Injection	Nominal Value	Unit		
Injection Processing (Melt) Temp	Nominal Value	Unit °C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

